

DIGITAL CENTRAL SUPERVISORY ALARM PANEL (OPTIONAL)

INPUTS

PPM DISPLAY & INDICATOR LIGHTS
UP TO 32 OF EACH OF THESE DETECTORS



LBW-420



LBW-WATCHMAN

RELAY &
4-20 mA
INPUTS

NO DISPLAY; INDICATOR LIGHTS ONLY
UP TO 32 OF EACH OF THESE DETECTORS



LBW-50



LBW-RLV

RELAY
INPUTS
ONLY



- STANDARD FEATURES
- 6-FIELD-ADJUSTABLE RANGES
 - STANDARD, 3-YEAR WARRANTY
 - HIGH PITCHED PIEZO ANNUNCIATOR
 - NEMA 4X, SAFETY YELLOW ENCLOSURE
 - GLOBAL EARLY WARNING (LOW ALARM) SILENCE
 - ZONE ALARM (HIGH ALARM) SILENCE
 - COMMON EARLY WARNING RELAY
 - COMMON ALARM RELAY

OUTPUTS



OPTIONAL
REMOTE
ALARM



OPTIONAL
IP SENSOR
APPLIANCE

OPTIONAL POWER SOURCES



POWER
SUPPLY &
TERMINAL
STRIPS

INTERNAL FOR:
DCSAP-8 & 16

SEPARATE BOX FOR:
DCSAP-24 & 32



UPS



OPTIONAL
OWNER'S
FIRE PANEL
SECURITY PANEL

OPTIONAL
OWNER'S
PLC/AUTOMATION SYSTEM